



IF IN DOUBT PLEASE ASK

D	Diameter (End)	10mm
Ds	Diameter (Shank)	10mm
L	Length Of Cutting Edge	28mm
Ls	Length to Shank	50mm
Dn	Shank Neck Diameter	9.5mm
Lo	Overall Length (Blank)	100mm
T	Taper Angle (OD)	
R	Corner Chamfer	0.15mm
N	Number Of Flutes	4
P	Primary Relief (OD)	
Rd	Raised Depth (OD)	
Rw	Raised Land (OD)	
Sw	Secondary Land Width	
F	Flute Depth	
Ra	Flute Rake (Hook)	
Ty	Relief style	
Pe	Primary Relief (End)	
Pl	Primary Land (End)	
Se	Secondary Relief (End)	
Da	Dish Angle (End)	
Ax	Axial Gash Angle	
h	Gash Pad Width	
H	Over Centre Length	
Y	Gash Web Thickness	
Hx	Helix Angle	
Ga	Gash Angle (L/S)	
Ro	Permissible Runout	
Rl	Raised Land Length	

QuickVend Location	
Quickgrind Stock	
QuickVend Stock	

Customer: Quickgrind

Customer Approval: Brian Pearce

Date: 26/9/22

CUSTOMER APPROVAL: Please check all drawing details, signing this document will signify customer acceptance and will be final. Signatory confirms that they are authorised to sign such documents on behalf of the company.

STEP	
FEED	
RPM	
TOOL LIFE	

REV.	DESCRIPTION	DATE


TITLE		Customer Drawing 4 Flute Carbide QVariLR 10mm x 28mm x 50mm Endmill XRed Coating	
PROPRIETARY DOCUMENT		BLANK CMD10L100	
This document is not to be copied or reproduced in whole or in part or communicated to third parties without the prior written consent of Quickgrind Ltd			
SIZE	SPECIAL I.D	QUICKGRIND PART NUMBER	REV
A4	272100	CE4S10x28-50C0.15FI1A2C	1
SCALE: 1 : 1		MATERIAL: Carbide	COATING: XRed

Unit 5701 Shannon Place, Shannon Way
Tewkesbury, Gloucestershire, GL20 8SL
T +44 (0)1684 294090 F +44 (0)1684 293168

Date: 26/9/22

Drawn: IV

Checked: KL



IF IN DOUBT PLEASE ASK